

SPECIFICATIONS

Programmable DC Power Supply

MODEL : EX150 - 4



ODA

TECHNOLOGIES
www.odacore.com

Parameter		Specifications	
Output rating(@0℃ ~ 40℃)	Voltage	0 to 150.0	Maximum 157.5
	Current	0 to 4.0	Maximum 4.200
Output WATT		0.7 KW	
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage	0.1% + 225.0mV	
	Current	0.1% + 12.0mA	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage	0.1% + 150.0mV	
	Current	0.1% + 8.0mA	
Ripple and Noise(20Hz to 20MHz)		≤ 50mVrms	
Load Regulation (with V-Sensing)		≤ 150 mV	
Line Regulation (with V-Sensing)		≤ 150 mV	
Resolution	Programming/Readback	≤ 2.5mV / ≤ 0.1mA	
	Display Meter	100mV / 1mA	
Temperature Coefficient After a 30-minute warm-up	Voltage	≤ 30.0mV	
	Current	≤ 1.2mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage	≤ 75.0mV	
	Current	≤ 2.0mA	
Voltage Programming Speed (10%~90% of output voltage)	Half load	Rising time	≤ 300ms
		Falling time	≤ 300ms
Remote Sensing Capability	Voltage Drop		Up to 2.5V per each lead
	Load Regulation		Add 5 mV to spec for each 1-volt change in the + output lead due to load current changes
	Load Voltage		Subtract voltage drop in load leads from specified output voltage rating.
OVP and OCP Accuracy ±(%of output + offset)	OVP		1% + 1.5V
	OCP		1% + 0.4A
	Activation Time		< 80ms when maximum output rating
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤ -0.8V
	Voltage Output Setting		No overshoot, No undershoot
Remote Interface		RS232C , RS485	
Programming Language		SCPI(Standard Commands for Programmable Instruments)	
Command Processing Time(average)	Apply	Setting	20ms
		Query	32ms
	Output Setting	Voltage & Current Setting	15ms
		Voltage & Current Query	32ms
	Measurement	Voltage & Current Query	32ms
	The Other	Setting & Query	< 35ms
State Storage Memory		Ten user-configurable(voltage,current,protection level)stored states	
Operation Temperature		0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling		Isolation DC FAN	
Output Terminal Isolated (maximum, from chassis ground)		±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
Insulating Resistance	Input - Output : ≥20MΩ		
	Input - Shell : ≥20MΩ		
	Output - Shell : ≥80MΩ		
Power Factor		0.98 Full load	
AC Input Ratings	Standard		single phase 220V ± 10% 50~60Hz
	Precision		6 month
Calibration Interval	Recommended		1 year
Dimensions (19" Standard)		70(W) * 125.5(H) * 400(D)	
Maximum Input Power(full load)		0.8 KW	
Weight	Net weight		4.2kg
	Gross weight		5.2kg

*상기모델은 사용자 Application에 최적화하기위해 예고없이 사양변경될 수 있으므로 구입전 확인하시기 바랍니다.