

SPECIFICATIONS

Programmable DC Power Supply

MODEL : EX300 - 32



ODA

TECHNOLOGIES
www.odacore.com

Parameter			Specifications	
Output rating(@0℃ ~ 40℃)	Voltage		0 to 300.0	Maximum 315.0
	Current		0 to 32.0	Maximum 33.6
Output WATT			10.6 KW	
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.1% + 450.0mV	
	Current		0.1% + 96.0mA	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.1% + 300.0mV	
	Current		0.1% + 64.0mA	
Ripple and Noise(20Hz to 20MHz)			≤ 100mVrms	
Load Regulation (with V-Sensing)			≤ 300 mV	
Line Regulation (with V-Sensing)			≤ 300 mV	
Resolution	Programming/Readback		≤ 5mV / ≤ 0.5mA	
	Display Meter		100mV / 10mA	
Temperature Coefficient After a 30-minute warm-up	Voltage		≤ 60.0mV	
	Current		≤ 9.6mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage		≤ 150.0mV	
	Current		≤ 16.0mA	
Voltage Programming Speed (10%~90% of output voltage)	Half load	Rising time	≤ 300ms	
		Falling time	≤ 300ms	
Remote Sensing Capability	Voltage Drop		Up to 2.5V per each lead	
	Load Regulation		Add 5 mV to spec for each 1-volt change in the + output lead due to load current changes	
	Load Voltage		Subtract voltage drop in load leads from specified output voltage rating.	
OVP and OCP Accuracy ±(%of output + offset)	OVP		1% + 3.0V	
	OCP		1% + 3.2A	
	Activation Time		< 80ms when maximum output rating	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤ -0.8V	
	Voltage Output Setting		No overshoot, No undershoot	
Remote Interface			RS232C , RS485 , USB Standard (TCP/IP Option)	
Programming Language			SCPI(Standard Commands for Programmable Instruments)	
Command Processing Time(average)	Apply	Setting	20ms	
		Query	32ms	
	Output Setting	Voltage & Current Setting	15ms	
		Voltage & Current Query	32ms	
	Measurement	Voltage & Current Query	32ms	
The Other	Setting & Query	< 35ms		
State Storage Memory			Ten user-configurable(voltage,current,protection level)stored states	
Operation Temperature			0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling			Isolation DC FAN	
Output Terminal Isolated (maximum, from chassis ground)			±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard	단상 220V ± 10% 50~60Hz		
		3상 380V ± 10% 50~60Hz		
	Option	단상 100V ± 10% 50~60Hz		
		단상 230V ± 10% 50~60Hz		
Calibration Interval	Precision		6 month	
	Recommended		1 year	
Dimensions (19" Standard)			426(W) * 176(H) * 550(D)	
Maximum Input Power(full load)			12.2 KW	
Weight	Net weight		34kg	
	Gross weight		35.5kg	

*상기모델은 사용자 Application에 최적화하기위해 예고없이 사양변경될 수 있으므로 구입전 확인하시기 바랍니다.